

Application  
for  
United States Letters Patent

To all whom it may concern:

*Be it known that we,* Markus ANDREASSON and Staffan SOLÉN

*have invented certain new and useful improvements in*

METHOD AND DEVICE FOR RECORDING OF INFORMATION

*of which the following is a full, clear and exact description.*

METHOD AND DEVICE FOR RECORDING OF INFORMATIONField of the Invention

The present invention relates to a method, a reading device, and/or a computer program for recording a bar code having a plurality of parallel lines of varying thickness.

Background Art

Bar codes are today used to a great extent in the industry, trade and other branches of business. They constitute a possibility of rationally identifying an object and recording an object passing a certain point. Several standards for bar codes are already established, such as European Article Numbering (EAN), Universal Product Code (UPC) etc.

A number of variants of bar code readers are presently available. The simplest type of bar code reader is the point sensor. A point sensor is passed by the user across the base, on which the bar code is printed. The point sensor then records the bar code as a variation in received light intensity.

A condition for the point sensor to record the information correctly is that the speed at which it is moved across the base is very even. If the point sensor has a comparatively high speed in a first portion of the bar code and a comparatively low speed in a second portion of the bar code, a line in the second portion will be interpreted as wider than an identical line in the first portion. Since the requirement for an even speed of motion is very high for this type of sensor, many reading attempts will fail. The most reliable method of achieving a correct reading of a bar code is to use a sensor the

point sensor as a bar code reader is thus associated with some problems, which makes its usability limited.

Another known method is to use an elongate sensor. It may consist of a row of juxtaposed CCD pixels (CCD = Charge Coupled Device). These absorb light from a surface, which is illuminated by a row of light-emitting diodes. This sensor is not passed across the bar code but is kept stationary over the same, all lines in the code being recorded simultaneously.

10 A drawback of the elongate sensor, in addition to its higher price, is that it cannot record bar codes of an arbitrary length. For each sensor of this type there is a certain maximum bar code length which is dependent on the number of pixels in the sensor and associated op-  
15 tics. Moreover, the elongate sensor can only with difficulty be used to record bar codes on a non-planar base.

A third prior-art method of recording a bar code is to use a bar code reader with a scanning laser. The bar code reader then comprises mechanically movable optics,  
20 which sweep a laser beam over a bar code. The received light is projected onto a point sensor.

The drawback of this type of bar code reader is above all a high price. However, the movable optics are also very susceptible to shocks, which restricts the us-  
25 ability of this bar code reader.

#### Summary of the invention

An object of the present invention is to wholly or partly remedy the above problems.

This object is achieved by a method for recording a bar code according to the present invention, a reading device  
30 for recording a bar code according to the present invention and a recording medium according to the present invention.

The invention is described in more detail in the following text, which is intended to illustrate the invention, but is not to be construed as limiting it.

prises the steps of:

- a) capturing, by means of a reading device, a sequence of two-dimensional images of at least portions of the bar code during moving of the reading device across the same;
- b) detecting the edges of the bar code in at least a subset of the images;
- c) determining, for the edges of at least a subset of the detected images, possible displacements in relation to the edges of a preceding image;
- d) determining the most probable sequence of displacements for the sequence of images; and
- e) reconstructing the bar code by means of said sequence of images and said most probable sequence of displacements.

By means of such a method, a bar code can be interpreted in a very reliable manner. The reading device can be moved across the bar code in an arbitrary fashion as long as the entire bar code is recorded. The speed of the motion may vary from immobile up to the speed at which two successive images do not overlap each other any longer. Bar codes of an arbitrary length can be recorded. The reading device can be accomplished at a very low cost. Merely by adding new software to a reading pen of the type as disclosed in International Patent Publication No. WO 92/01440/A1, directed to pen input text, a reading device for interpretation of bar codes can be accomplished. A person who for other purposes owns such a reading pen can thus at a very low cost provide a bar code reader which operates according to the inventive method.

A similar computerized method, detection is

not to be taken as limiting the scope of the invention. The invention is defined by the claims.

Preferably step b) comprises the following steps:

b1) generating, for at least a subset of the images which represent parts of the bar code, a histogram corresponding to the darkness level in said pixel along said  
5 band; and

b2) differentiating said histogram so that a sequence of edge coordinates is provided, which describe where along said band in the image the edges of the lines of the bar code are located. This results in a more reliable  
10 detection of the bar code.

According to a preferred embodiment, differentiated histograms are generated for a plurality of bands extending over an image at different angles, the band whose differentiated histograms have the highest peaks being  
15 selected as the band which is essentially perpendicular to the direction of extension of the lines of the bar code. As a result, the bar code can be detected even if the reading device is rotated during the motion. Preferably differentiated histograms are generated for  
20 more bands in the first image of the image sequence than in subsequent images. This enables quicker data processing for subsequent images.

An edge coordinate can preferably be determined more accurately by maximizing an approximating function, such  
25 as a second degree function, which runs through the points forming the corresponding peak in said differentiated histogram. This allows a more exact detection of the edges of the bar code.

Preferably possible displacements are determined in  
30 step c) by assuming such a displacement that two edge coordinates belonging to successive images correspond to each other, and then determining whether the remaining

the remaining edge coordinates of the bar code can be detected by the same method.

eration of the reading device. This enables reliable detection of the bar code.

Preferably, error functions are determined in step d) for the images in which edges have been detected, for at least a subset of the conceivable displacements relative to the displacements of a preceding image. This makes it possible to determine a most probable displacement.

Such an error function,  $e_{k,j}$ , can preferably be calculated as follows:

$$e_{k,j} = \max[e_{k,j-1}, (v_k - v_{k,j-1})(a_k - a_{k,j-1})]$$

wherein

$e_{k,j-1}$  = error function of the displacement of a preceding image,

$v_{k,j-1}$  = speed of the reading device when the preceding image was captured if the displacement of the preceding image is valid,

$v_k$  = speed of the reading device when the image in question was captured if the displacement of the image in question is valid,

$a_{k,j-1}$  = acceleration of the reading device when the preceding image was captured if the displacement of the preceding image is valid,

$a_k$  = acceleration of the reading device when the image in question was captured if the displacement of the image in question is valid.

Such an error function has been found to be very reliable.

For the last image in the image sequence, the displacement relative to displacements of the preceding image, which has the lowest error function, is suitably selected as the most probable displacement. This results in more reliable detection of the bar code.

As the error function is calculated for each displacement, the error function for the displacement which has the lowest error function is selected as the most probable displacement.

According to a second aspect, the present invention relates more specifically to a reading device for recording a bar code, which consists of a plurality of parallel lines of varying thickness. The reading device comprises means for capturing a sequence of two-dimensional images of at least portions of the bar code when moving the reading device across the same, means for detecting the edges of the bar code in at least a subset of the images, means for determining possible displacements in relation to the edges of a pre-reading image for the edges of at least a subset of the detected images, means for determining the most probable sequence of displacements for the sequence of images, and means for reconstructing the bar code by means of said sequence of images and said most probable sequence of displacements.

The reading device involves advantages corresponding to those of the above-described method and can be varied correspondingly. Then the reading device generally comprises means for carrying out the steps defined in the method.

According to a preferred embodiment, the reading device can be included in a reading pen. The reading device can then be accomplished by adding software to such a reading pen as disclosed in International Patent Publication No. WO 98/20446, A1.

The reading device can also be integrated in other types of equipment, of any other type, such as a mobile telephone. Then the reading device can be used, for instance, to record a telephone number.

According to a third aspect, the present invention relates more specifically to a digital storage medium comprising a computer program for recording a bar code,

b) detecting the edges of the bar code in at least a subset of the images;

c) determining possible displacements in relation to the edges of a preceding image for the edges of at least  
5 a subset of the detected images;

d) determining the most probable sequence of displacements for the sequence of images; and

e) reconstructing the bar code by means of said sequence of images and said most probable sequence of displacements.  
10

This computer program involves advantages corresponding to those of the above-described method and can be varied correspondingly. Then the computer program generally comprises instructions for carrying out the steps  
15 defined in the method.

#### Brief Description of the Drawings

Fig. 1 illustrates a reading device in which a method according to the present invention can be applied.

Figs 2a-2c show a method according to the present  
20 invention.

Fig. 3 shows schematically an image representing a bar code.

Fig. 4a shows an image of a bar code.

40 Figs 4b-4c show histograms for different bands over  
25 the bar code image in Fig. 4a.

Figs 4d-4f show differentiated histograms corresponding to the histograms in Figs 4b and 4c, respectively.

Fig. 4g shows an enlarged detail from the histogram  
30 in Fig. 4a.

Figs 5a-5i show how conceivable displacements between two successive images are determined.



### Description of Preferred Embodiments

Fig. 1 shows a reading device in which a method according to the present invention can be applied.

The reading device 100 can preferably resemble the type disclosed in International Patent Publication No. WO 93/20446, A1, the description of which is incorporated herewith by reference. This reading device, however, is used for recording of text.

The reading device 100 according to the invention then has a casing 101, which resembles an ordinary high-lighter. The reading device 100 can in a preferred embodiment also be used for inputting of text. The reading device 100 can also be integrated with other equipment, such as mobile telephones, Personal Digital Assistants (PDA's), digital cameras etc.

In one short side of the casing there is a window 102 which is to abut against or be held at a short distance from the base from which reading is intended to occur. The width and height of the window 102 essentially conform with the surface reproduced by the reading device 100 as an image is being captured. The window 102 forms an acute angle to the longitudinal axis of the casing of the reading device, so that the user of the reading device 100 is made to hold the reading device 100 at a certain predetermined angle to the base. The window 102 is slightly retracted into the casing 101 and need not be flush against the base on the side of the reading device 100.

The casing contains essentially an optics part 103, an electronic circuitry part 104 and a power supply part 105.

Fig. 2 shows a side view of the reading device 100 according to the present invention.

The casing 101 is made of a material which is transparent to the light from the base, which is to be read, and which is also transparent to the light from the reading device 100.

to distribute the light. The purpose of the lens system 107 is to project an image of the part of the base positioned under the window 106 on the light sensitive sensor 108. The light-sensitive sensor is preferably a two-dimensional CCD sensor with a built-in analog-to-digital (A/D) converter.

The power supply unit 105 comprises a battery 112, which is mounted in the casing 101.

The electronic circuitry part 104 comprises a processor and data memories for processing images recorded by the light-sensitive sensor 108. A reading device according to the invention comprises means for carrying out the method steps that will be described below. These means suitably consist of said processor and memories provided with appropriate software. Part of or the entire recording method may also be carried out by means of an Application Specific Intergrated Circuit (ASIC).

The inventive storage medium can consist of one of the above-mentioned memories in the reading device but can also be another storage medium, such as a diskette or a hard disk connected to a server.

The electronic circuitry part 104 also comprises a transmitter for transmitting information, for instance to a personal computer. This can be of the type infrared (IR) transmitter, or a short range radio transmitter, for instance according to the BLUETOOTH standard.

FIG. 1 is a schematic view of the method according to the present invention. The reading device described above captures at regular interval images of the base across which it is being passed. In a preferred embodiment the image frequency is 1 Hz. The process in which the method of the present invention is carried out thus

comprises the steps of: (a) providing a reading device as described above; (b) passing the reading device across the base to be read; (c) capturing images of the base at regular intervals; (d) processing the images to extract the data; (e) storing the data in a storage medium; (f) transmitting the data to a personal computer; (g) displaying the data on a screen.

soon as the first image has been captured.

The reading device can be used for other purposes than entering of bar codes; for instance text, digits and other types of symbols can be entered. When the process  
5 through which the inventive method is carried out receives 201 (see Fig. 2a) an image, it is checked 202 whether the received image is a bar code.

This check can be carried out relative to a set criterion. For instance, it is possible to identify the pixels  
10 located in the edges of the lines, i.e. black pixels which have a white neighboring pixel on their right or left side, or alternatively above or below them. Subsequently, calculation, both vertically and horizontally, of the total length of continuous rows/columns having a  
15 length greater than one, of such edge pixels is carried out. If the ratio between the total length seen in the vertical direction (columns) and the total length in the horizontal direction (rows) exceeds a certain value, the image probably shows a bar code. This method for recog-  
20 nizing a bar code can also be used separately in other applications than in the method according to the present invention.

If the captured image does not describe a bar code, it is to be processed 203 in another manner. This may im-  
25 ply, for example, that recording of text occurs according to what is known from International Patent Publication No. WO 88/01440, A1. If the captured image describes a bar code, it is to be processed as the first image in a sequence of images describing the bar code.

30 First, a number of histograms 204 (see Figs 4b, 4c) are generated, which describe the darkness level of the pixels along a number of bands 401, 402 etc. (see Fig.

Extending beyond the scope of the present invention is the use of the present invention for the purpose of detecting and identifying objects in a scene.

value of the darkness degree of the pixels along the width of the band suddenly changes (see Fig. 4c) where the band extends over the edge of a line. In a histogram corresponding to a band 401 which extends more obliquely over the bar code, the total value of the dark-ness degree (on a gray scale) of the pixels over the width of the band will, however, change more slowly (see Fig. 4b), since pixels along the width of the band can be positioned on both sides of the edge of a line. By histogram is here generally meant a logic structure, such as a vector, which describes the darkness degree in different positions along the length of the band. In fact, the histogram need normally not be printed, but is here shown only for descriptive purposes.

With reference once more to Fig. 2a, the above generated histograms are differentiated 205, i.e. on the basis of each histogram a new histogram is generated, which describes the difference in level between two neighboring points in the previously generated histogram. Figs 5a and 5b show differentiated histograms corresponding to those in Figs 4c and 4b, respectively.

Using a criterion which takes the height of the peaks in these differentiated histograms into consideration, the differentiated histogram corresponding to the most perpendicular band over the bar code is selected 25, with reference made to Fig. 2a. For example, the sum of the square of the values of the differentiated histogram along the band can then be calculated. The most perpendicular band gives the highest peaks and thus the highest value of the square sum. Alternatively the sum of absolute values of the histogram level can be calculated. The peaks constitute a rough estimate of the position of

the position of the band over the bar code. The position of the band is then determined by the position of the peaks.

histogram in Fig. 5a, more specifically a peak, which represents a transition from white to black. As appears from Fig. 5c, this peak consists of three successive bars 501, 502, 503. An approximation of the second degree 504 of these bars is effected, and the maximum of this approximation of the second degree is calculated. The edge of the line can now be assumed to be very close to this maximum and is thus determined on the sub-pixel level, i.e. with a higher resolution than the resolution of the 10 pixels. By carrying out such interpolations of all peaks in the selected differentiated histogram, a set of edge coordinates is obtained, where the position of the edges along the selected band is most exactly determined. By edges is generally meant transitions from white to black 15 and vice versa, but of course other colors may occur.

The set of edge coordinates can be made as an up/down set where all edges are included, or as separate up sets (white to black) and down sets (black to white). The position of the edges in the first image thus is determined. 20

With reference to Fig. 2b, the next image is then received 203. Similarly to the first image, histograms of the darkness level of the pixels in bands over the image are generated 209. For images following the first image 25 it is, however, normally not necessary to generate histograms for a large number of bands at different angles over the image. If the image frequency is 4 Hz, only 20 ms have passed since the preceding image was captured, and therefore it can be assumed that the angle of the 30 reading device to the base has not changed to any considerable extent. Therefore only histograms for three different bands are generated, at the angle which in the

image.

These three histograms are differentiated 210 and the histogram having the highest peaks is selected as the most perpendicular. In the same way as for the first image, interpolation 211 is carried out to determine the position of the edges of the lines of the bar code in the band on the sub pixel level.

Subsequently, conceivable displacements of a later image 505 (Fig. 5, corresponding to image 7 in Fig. 8a) in relation to the preceding image 506 (image 6 in Fig. 8a) are determined, which is illustrated with reference to Figs 6a-6d. This occurs in such manner that the sets of edge coordinates, here shown as lines upwards and downwards along an axis, of the two images are compared. For example, the up-coordinate 501 (transition from white to black) in the preceding image 506 which is furthest to the right can be set as a reference point. The up-coordinates 502, 503, 504 etc. of the subsequent image then provide proposals for displacements A1, A2, A3, A4 of the reading device to the right. For each of these proposals, it is decided whether down-coordinates and the other up-coordinates coincide. In that case, this displacement is conceivable.

In Fig. 6a, the up-coordinate of the later image which is positioned furthest to the left is assumed to conform with the up-coordinate of the preceding image 506 furthest to the right, which results in a displacement A1 to the right. Then also the down-coordinate which is furthest to the right in the preceding image 506 conforms with the down-coordinate which is positioned furthest to the left in the later image 505. No other coordinates are present within the overlap of the images,

which is possible only if the images are perfectly aligned. In this case, the displacement A1 is the only conceivable displacement.

ceding image 606 furthest to the right, which gives the displacement A2. Then also the two down-coordinates which are positioned furthest to the right in the preceding image 606 conform with the two down-coordinates which are positioned furthest to the left in the later image 605. At the same time, the two up-coordinates which are positioned furthest to the right in the preceding image 606 conform with the two up-coordinates which are positioned furthest to the left in the later image 605. A2 therefore is a conceivable displacement.

In Fig. 6c, the up-coordinate of the later image which is positioned furthest to the left but two is assumed to conform with the up-coordinate of the preceding image 606 furthest to the right, which gives the displacement A3. Then also the three down-coordinates which are positioned furthest to the right in the preceding image 606 conform with the three down-coordinates which are positioned furthest to the left in the later image 605. At the same time the three up-coordinates which are positioned furthest to the right in the preceding image 606 conform with the three up-coordinates which are positioned furthest to the left in the later image 605. Therefore A3 is a conceivable displacement.

In Fig. 6d, the up-coordinate of the later image, which is furthest to the left but three, is assumed to conform with the up-coordinate of the preceding image 606 furthest to the right, which gives the displacement A4. However, here are conflicts between several of the other coordinates in the different images. For example, the up-coordinate which is furthest to the right but one in the preceding image 606 has no correspondence in the later image. Thus A4 is not a conceivable displacement.

displacement is conceivable or not is determined according to a certain criterion. For instance, the square sum of deviations in pairs of up and down coordinates of the overlapping parts of each image can be calculated (for  
 5 instance, the difference between the coordinate value of the lowest up-coordinate in the overlapping part of the first image and the coordinate value of the lowest up-coordinate in the overlapping part of the later image). If the square sum of these deviations is below a certain  
 10 value, the displacement is assumed to be possible.

To be able to detect also motions from the left to the right, also the corresponding method can be carried out where, for example, the up-coordinates furthest to the left in the preceding image are used as a reference  
 15 point.

For most pairs of images in the sequence, which reproduce the bar code, it is probable that more than one conceivable displacement will be found. It is established  
 213 by the process whether conceivable displacements with regard to the preceding image exist. If no conceivable  
 20 displacements exist, this means that the recording of the bar code has been terminated and that the final processing is to take place as will be described below with reference to Fig. 2c.

If, however, valid displacements exist, there is determined 214 a set of these in order in function with regard to the displacement of the preceding image. This is shown in Fig. 7, which includes a diagram with a horizontal time axis whereas the amount of  
 25 displacement between successive images is disposed in the direction of the vertical axis. Between the first image 701 and the second image 702 there is a set 703

of displacements 704, 705, 706, 707, 708, 709, 710, 711, 712, 713, 714, 715, 716, 717, 718, 719, 720, 721, 722, 723, 724, 725, 726, 727, 728, 729, 730, 731, 732, 733, 734, 735, 736, 737, 738, 739, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 750, 751, 752, 753, 754, 755, 756, 757, 758, 759, 760, 761, 762, 763, 764, 765, 766, 767, 768, 769, 770, 771, 772, 773, 774, 775, 776, 777, 778, 779, 780, 781, 782, 783, 784, 785, 786, 787, 788, 789, 790, 791, 792, 793, 794, 795, 796, 797, 798, 799, 800, 801, 802, 803, 804, 805, 806, 807, 808, 809, 810, 811, 812, 813, 814, 815, 816, 817, 818, 819, 820, 821, 822, 823, 824, 825, 826, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 844, 845, 846, 847, 848, 849, 850, 851, 852, 853, 854, 855, 856, 857, 858, 859, 860, 861, 862, 863, 864, 865, 866, 867, 868, 869, 870, 871, 872, 873, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 898, 899, 900, 901, 902, 903, 904, 905, 906, 907, 908, 909, 910, 911, 912, 913, 914, 915, 916, 917, 918, 919, 920, 921, 922, 923, 924, 925, 926, 927, 928, 929, 930, 931, 932, 933, 934, 935, 936, 937, 938, 939, 940, 941, 942, 943, 944, 945, 946, 947, 948, 949, 950, 951, 952, 953, 954, 955, 956, 957, 958, 959, 960, 961, 962, 963, 964, 965, 966, 967, 968, 969, 970, 971, 972, 973, 974, 975, 976, 977, 978, 979, 980, 981, 982, 983, 984, 985, 986, 987, 988, 989, 990, 991, 992, 993, 994, 995, 996, 997, 998, 999, 1000.



image 702 and the third image 704 there is a set 705 containing two conceivable displacements. In this case however, both are positive, which corresponds to motions of the reading device to the right at different speeds.

5 For all displacements between the preceding and subsequent images in the sequence, error functions are determined, as mentioned above, relative to all displacements in the displacements of the preceding set. For example, for the greatest displacement 706, between  
10 the second 702 and the third 704 image, error functions are determined relative to the set 703 of conceivable displacements 707, 708, 712 between the first 701 and the second 702 image.

The error function  $e_i$  can preferably be written as  
15 follows:

$$e_i = \max[e_{i-1}, (v_i - v_{i-1})(a_i - a_{i-1})]$$

wherein

$e_{i-1}$  = error function of the displacement of a preceding image,

20  $v_{i-1}$  = speed of the reading device when the preceding image was captured if the displacement of the preceding image is valid,

$v_i$  = speed of the reading device when the image in question was captured if the displacement of the image in  
25 question is valid,

$a_{i-1}$  = acceleration of the reading device when the preceding image was captured if the displacement of the preceding image is valid, and

$a_i$  = acceleration of the reading device when the  
30 image in question was captured if the displacement of the image in question is valid.

It is the difference in the speed required for the dis-

placement of the reading device between the preceding image and the image in question, multiplied by the difference in the acceleration of the reading device between the preceding image and the image in question.

vice. Even if the differences in speed and acceleration are small, a great error will, however, be given if the preceding displacement had a great error, since this error then propagates in the maximum function. Speed is  
 5 here measured in the number of pixels (integer or real number) perpendicular to the lines of the bar code between two captured images.

For each conceivable displacement in an image, the displacement of the preceding image which has the lowest  
 10 error function is selected (Fig. 2b, 215) as the most probable preceding displacement. For the greatest conceivable displacement 706 between the second 702 and the third 704 image, for instance the positive displacement 707 (i.e. to the right) between the first 701 and the  
 15 second 702 image is selected as the most probable preceding displacement. In Fig. 7 each displacement points at its most probable preceding displacement. An example of a less probable preceding displacement is indicated with a dashed line.

20 Subsequently the process is repeated, once more with reference to Fig. 2b, when the next image is received 208.

When the process establishes 216 that no conceivable displacements relative to the preceding image exist for  
 25 an arrived image, the scanned bar code is finally processed, as will be described in more detail with reference to Fig. 3a.

For the last image which had conceivable displacements relative to the preceding image and which thus was  
 30 the last image describing the bar code, it is established 217 which displacement relative to displacements of the preceding image had the lowest error function. This dis-

can now be created 218.

This chain 709 in Fig. 7 of most probable displacements forms a set of displacements which together with the edge coordinates in each image can be used to reconstruct the edge coordinates for the entire bar code into a global set of edge coordinates. This global set of edge coordinates describes the appearance of the bar code, provided that the entire bar code has been imaged. Consequently, the set of edge coordinates can be used to extract 220 the information contents of the bar code, in manners well known per se.

An example of the method is shown in Figs 8a and 8b. A bar code 801, in this case according to the EAN 13 Standard, is recorded. The symbol value of the bar code, i.e. the information that is to be extracted, is the string "7331424310072". Twelve images of the bar code are captured when a reading device is passed across the bar code 801. The positions of the first and the seventh image are indicated in Fig. 8a. From these twelve images, a set of edge coordinates 802, 803 etc. is produced. These are shown as diagrams in Fig. 8a. When displacements  $\Delta 2$ ,  $\Delta 3$  etc. between preceding and subsequent images have been determined, as shown in Fig. 8b, a global set of edge coordinates 804 for the entire bar code can be produced. The global set of edge coordinates 804 is then used to extract the information contents 805 of the bar code. This occurs in a manner similar to that of prior art bar code readers.

The method according to the invention can generally be described with the following steps:

a) capturing by means of the reading device a sequence of  $n$  individual images of at least part of

the bar code to be read;

b) determining the relative displacements  $\Delta 1, \Delta 2, \dots, \Delta n$

the edges of a preceding image for the edges of at least a subset of the detected images;

d) determining the most probable sequence of displacements for the sequence of images; and

5 e) reconstructing the bar code by means of said sequence of images and said most probable sequence of displacements.

Normally, each image comprises a portion of a bar-code. However, at bar-codes with small length the  
10 complete bar-code maybe included in one image. In this case, several images of the same bar-code may increase this accuracy by taking a mean value.

The invention is not restricted by the embodiments described above and can be varied in several ways within  
15 the scope of the appended claims.